

TURNSTILE

F1

VERSIONS:

GA2-F1

ZA2-F1
(MOTOR)



Designed with passion

Prepared by the best designers




Quick and Easy Setup

DEVICE DESCRIPTION

The device designed to assist pedestrian access control at guarded passage ways inside buildings.

Examples of use:


- points of ticket control and access control for passenger traffic,
- airports/seaports,
- passages for authorised personnel, directing passenger traffic,
- points of access control in secured buildings (e.g. state offices such as border crossing points, other services),
- points of ticket control and fees at museums, theatres, cinemas, exhibitions, fair areas, show facilities, paid toilets, points of ticket control at sports facilities, e.g. swimming pools, stadiums, other sports and show facilities,
- access and time attendance control points in working places, e.g. offices, dedicated areas in factories.





The subtle form and stable shape add a new dimension to the facility

DEVICE DESCRIPTION



FINISH OPTIONS



■ Stainless steel - INOX AISI 304




□ RAL 9006



□ RAL 7016



□ RAL 9003



□ RAL 5010



□ RAL 6002

- Standard finish
- Non-standard colour/non-standard finishing



DEVICE CONTROLLER

IMPORTANT FEATURES

MAIN INPUTS / OUTPUTS

QUEUE LENGTH CONFIGURATION (SIGNAL MEMORY)	ENTRY	
	CARD READER	BUTTON
DISPLAYING OPERATION PARAMETERS / CONFIGURATION OF WORKING MODES	EXIT	
	CARD READER	BUTTON
LANGUAGE SELECTION	INFORMATION ON THE EXECUTION OF THE TRANSITION CYCLE	
	FEEDBACK (ENTRY)	FEEDBACK (EXIT)
CONFIGURATION OF UNLOCKING TIME / FEEDBACK CONFIGURATION	INPUT (LOCK)	
	TO LOCK TRANSITION SECTION E.G. WITH A METAL DETECTOR OR BMS	
TEST MODE / CALIBRATION	INPUT (FIRE PROTECTION)	
	TO UNLOCK TRANSITION SECTION E.G. WITH A FIRE PROTECTION SYSTEM	



MODEL ZA2

VERSION WITH MOTOR



CONTROL: MAGTRONIC
The mechanism is adapted to work with the MACTRONIC electronic system enabling, among others, settings of operating modes, diagnostics, control with external systems.



MODES OF OPERATION
The device enables operation in various modes, e.g. pedestrian traffic control for both traffic directions or pedestrian traffic control for any selected traffic direction.



EASY CONFIGURATION
Operation modes and functions can be easily configured via the control panel with display and manipulator.



LED PICTOGRAMS
Visual signaling (diode pictograms) inform about the directions of possible traffic in the crossing section that are turned on and off.



PRECISE ROTOR POSITION MEASUREMENT SYSTEM
The device is equipped with an electronic rotor position measurement system, which, using an encoder, allows you to control the operation of the locking system and smooth rotor movement.



SOUND SIGNAL
The device is equipped with an acoustic signaling device activated, among others, by when forcing the rotor arm.



ASSISTING MOVEMENT OF ROTOR
The mechanism of the device is equipped with an electromechanical system supporting the rotation of the arms (motor).



LOCKING SYSTEM
The device has a system that unlocks the device in the event of a power failure.



ARM DROP FUNCTION (ADDITIONAL OPTION)
Automatic arm drop function in case of power failure (this function is available in the device model with the arm drop module).

MODEL GA2



CONTROL: MAGTRONIC
The mechanism is adapted to work with the MACTRONIC electronic system enabling, among others, settings of operating modes, diagnostics, control with external systems.



MODES OF OPERATION
The device enables operation in various modes, e.g. pedestrian traffic control for both traffic directions or pedestrian traffic control for any selected traffic direction.



EASY CONFIGURATION
Operation modes and functions can be easily configured via the control panel with display and manipulator.



LED PICTOGRAMS
Visual signaling (diode pictograms) inform about the directions of possible traffic in the crossing section that are turned on and off.



MECHANICAL ROTOR POSITIONING
The device has a mechanical system for positioning the rotor arms.



ASSISTING MOVEMENT OF ROTOR
The mechanism of the device is equipped with a mechanical-pneumatic system supporting the rotation of the arms.



LOCKING SYSTEM
The device has a system that unlocks the device in the event of a power failure.



ARM DROP FUNCTION (ADDITIONAL OPTION)
Automatic arm drop function in case of power failure (this function is available in the device model with the arm drop module).

DEVICE MODELS

	MODEL	MECHANISM	MECHANISM	ARM DROP"DA"	COVER WITH HOLES FOR THE READER "R"
		ZA2	GA2		
WITH MOTOR	ZA2-F1-INOX	•			
	ZA2-F1-RAL	•			
	ZA2-F1-DA-INOX	•		•	
	ZA2-F1-DA-RAL	•		•	
	ZA2-F1-R-INOX	•			•
	ZA2-F1-R-RAL	•			•
	ZA2-F1-DA-R-INOX	•		•	•
	ZA2-F1-DA-R-RAL	•		•	•
	GA2-F1-INOX		•		
	GA2-F1-RAL		•		
	GA2-F1-DA-INOX		•	•	
	GA2-F1-DA-RAL		•	•	
	GA2-F1-R-INOX		•		•
	GA2-F1-R-RAL		•		•
	GA2-F1-DA-R-INOX		•	•	•
	GA2-F1-DA-R-RAL		•	•	•

PARAMETERS

Power supply voltage:	~24 V AC	
Peak current:	70 VA	
Minimum power consumption:	3 A	
Control signal:	max. 1 sec	
Feedback signal:	0V	
Operating temperature:	-25° to +50° C [-13° to 122°F]	
Storage temperature:	-30° to +60° C [-22° to 140°F]	
Realive humidity:	10-80%	
Operating environment:	inside/outside of buildings*	
IP protection rate:	IP 40	
Net weight: ~ [kg/lbs]:	GA2	ZA2
	~60 / ~132	~49 / ~108

* - under the roof

ADDITIONAL OPTIONS

POSTS *

UP-1



SCM1



SW-1-ARM



CONTROL PANELS *

P1




P2




PLATFORMS *

PSN-1



PSN-2




POWER SUPPLY *



* Optional equipment not included in the equipment of the device.

DIMENSIONS



- KEY:
- External control signal - S/UTP cable
 - 24 V supply - ØMY wire 3x1.5mm
 - Foundation

All information given herein is valid at time of publication. GASTOP reserves the right to introduce changes to this offer, concerning both models as well as their construction and equipment. This document does not constitute an offer as understood by law and is published solely for the purpose of information. Optional equipment presented in this brochure may not be available. Product photos and visualizations presented herein may not accurately show technologies in use, properties of materials or colors. Please refer to an authorized distributor or directly to the device manufacturer for detailed information on the above mentioned parameters.

Notes:



EU: GASTOPGROUP.COM
USA: GASTOP.US

Händler

MADE IN E.U.