

# Interfaces and internal expansions

## TP8-28 & TP-28 GSM

### ESP4-20



Approved for homologated control units



#### Compatibility

TP8-28

TP8-28 GSM

#### Mounting position

A

B

C

D

Expansion card with 4 parallel zone inputs.  
These inputs enable the wiring of conventional detectors and Zone Bus.

Item no. F127TP420ESP / ATA211

### TP PROX



Approved for homologated control units



#### Compatibility

TP8-28

TP8-28 GSM

#### Mounting position

A

B

C

D

Connection interface module for proximity key readers; you can connect to the interface up to 4 readers in parallel.

Item no. F127TPPROX / ATA225

### TP OUT60C



Approved for homologated control units



#### Compatibility

TP8-28

TP8-28 GSM

#### Mounting position

A

B

C

D

6 logical output open collector expansion module. The 6 fully programmable outputs can be freely associated with the logical outputs managed by the system.

Item no. F127TPOUT60C / ATA215

### TP OUTREL



Approved for homologated control units



#### Compatibility

TP8-28

TP8-28 GSM

#### Mounting position

A

B

C

D

1 relay output expansion module with free exchange. The fully programmable output can be freely associated with the logical outputs managed by the system.

Item no. F127TPOUTREL / ATA216