



Input expansions

The versatile and modular structure can be considered an intrinsic characteristic of the Tecnoalarm systems, characteristic which the RSC® range of the input expansions fully meet. The range includes three models able to satisfy any installation requirement and guarantee an efficient use of the system's RSC® resources.



SPEED 4-8 P3A								
	Compatible systems: TP10-42 - TP8-88 - TP20-440 Expansion module with 1 Sensor Bus port for the connection of 8 RSC® detectors from Tecnoalarm and 4 inputs for the connection of conventional RDV® and Zone Bus detectors - 1 Siren Bus port for the connection of 1 RSC® sirens - 4 programmable logic outputs - 3A switching power supply - 12V/12Ah battery - Connection via RS485 serial bus - Metal casing - Dimensions (L x H x D) 315 x 260 x 108mm - Certified to EN 50131-6 - Security grade 2 or 3 (depending on current and autonomy)							
	Item no. F101SPEED48P3A				Ref. Nestor: ATA236			
SPEED ALM8 PLUS								
	Compatible systems: TP8-28 - TP8-28 GSM - TP10-42 - TP8-88 - TP20-440 Expansion module with 4 Sensor Bus ports for the connection of 8 RSC® detectors from Tecnoalarm - 1 Siren Bus port for the connection of RSC® sirens - 4 programmable outputs - 1.8A switching power supply - 12V/7Ah battery - Connection via RS485 serial bus - Antistatic ABS casing - Design by Pininfarina - Dimensions (L x H x D) 350 x 285 x 93mm							
	Item no. F101SPEALM8PLUS				Ref. Nestor: ATA224			
SPEED 8 PLUS								
	Compatible systems: TP8-28 - TP8-28 GSM - TP10-42 - TP8-88 - TP20-440 Expansion module with 1 Sensor Bus port for the connection of 8 RSC® detectors from Tecnoalarm 2 programmable outputs - Connection via RS485 serial bus - Dimensions (L x H) 124 x 68mm - ABS casing (optional) <i>N.B. Compatible casings C100P and C90</i>							
	Item no. F101SPEED8PLUS				Ref. Nestor: ATA218			
SPEED 4 PLUS								
	Compatible systems: TP8-28 - TP8-28 GSM - TP10-42 - TP8-88 - TP20-440 Expansion module with 1 Sensor Bus port for the connection of RSC® detectors from Tecnoalarm and 4 inputs for the connection of RDV® and Zone Bus detectors from Tecnoalarm as well as conventional detectors - 1 programmable output - Connection via RS485 serial bus - Dimensions (L x H) 124 x 68mm - ABS casing (optional) <i>N.B. Compatible casings C100P and C90</i>							
	Item no. F101SPEED4PLUS				Ref. Nestor: ATA217			

EXPANSIONS MODULES - Accessories

	C100P ABS casing - Design by Pininfarina - Dimensions (L x H x D) 270 x 156 x 68mm - White color Item no. C110C100P ATA231		C90 ABS casing - Dimensions (L x H x D) 165 x 110 x 41mm - White color Item no. C110C90 ATA230
--	---	--	---