



RS485 Pininfarina nexion		 Approved for homologated control units							
LCD300/S		Compatibility		TP8-28	TP8-28 GSM	TP8-88	TP8-96 VIDEO	TP16-256	TP16-512
		Programming and management console. 2X16 character LCD-display with backlight. Integrated speech interface. Program Management max.15. RS485 bus connection. Surface Mount. Elegant design by Pininfarina. Antistatic ABS enclosure. Dimensions (LxHxD) 120x175x46mm. White.							
Item no. F127LCD300S		/ATA303							
LCDPROX1		 Approved for homologated control units							
Compatibility		TP8-28	TP8-28 GSM	TP8-88					
		Programming and management console. Back-lit LCD graphics display. Integrated reader for proximity keys PROX KEY. Program Management max. 8. RS485 bus connection. Surface Mount. Refined and elegant design. Antistatic ABS enclosure. Dimensions (LxHxD) 150x119x35mm. White.							
Item no. F127LCDPROX1		/ATA304							
LCD020									
Compatibility		TP4-20	TP4-20 GSM						
		Programming and management console. 2X16 character LCD-display with backlight. Program Management max. 4. Displays the status of 20 zones. RS485 bus connection. Surface mounting. Antistatic ABS enclosure. Dimensions (LxHxD) 150x119x35mm. White. <i>Note: the console LCD020 can only be used as an alternative to the console LCD012 and LED06.</i>							
Item no. F127LCD020									
LCD012									
Compatibility		TP4-20	TP4-20 GSM						
		Programming and management console. 2X16 character LCD-display with backlight. Program Management max. 4. Displays the status of the first 12 zones. RS485 bus connection. Surface Mount. Antistatic ABS enclosure. Dimensions (LxHxD) 150x119x35mm. White. <i>Note: the console LCD012 can only be used as an alternative to the console LCD020.</i>							
Item no. F127LCD012		/ATA301							
LED06									
Compatibility		TP4-20	TP4-20 GSM						
		Management console. Signals with LED. Program Management max. 4. Displays the status of the first 6 zones. RS485 bus connection. Surface Mount. Antistatic ABS enclosure. Dimensions (LxHxD) 140x80x28mm. White. <i>Note: the console LED06 can only be used as an alternative to the console LCD020.</i>							
Item no. F127LED06									