

Consoles

LCD300/S	 Approved for certified systems EN 50131	 CODES	 VOICE SYNTHESIS	 15 PROGRAMS MANAGED
	Console with backlit 2x16 characters LCD, voice synthesis function (connection of S wire from the control panel required) and acoustic signaling device - Management of 15 programs - RS485 connection - Anti-tamper protection against opening and detachment - Stylish Pininfarina design - Antistatic ABS casing - Surface mounting - Dimensions (L x H x D) 120 x 175 x 46mm - White - EN 50131 (approved for use with certified systems)			
	Item no. F127LCD300S (while stock last)			

LCDPROX1	 Approved for certified systems EN 50131	 CODES	 RFID READER	 8 PROGRAMS MANAGED
	Console with backlit graphic LCD and integrated RFID reader - Management of 8 programs - RS485 connection - Anti-tamper protection against opening and detachment - Stylish design - Antistatic ABS casing - Surface mounting - Dimensions (L x H x D) 150 x 119 x 35mm - White - EN 50131 (approved for use with certified systems)			
	Item no. F127LCDPROX1			

RFID reader interfaces

TP SKN	 Approved for certified systems EN 50131	 TRANSPONDER INTERFACE	 4 UNITS MANAGED
	Interface for connecting up to 4 RFID readers of the type ATPROX - RS485 connection - ABS casing - Surface mounting - Dimensions (L x H x D) 63 x 101 x 25mm - White - EN 50131 (approved for use with certified systems)		
	Item no. F127TP-SKN		