



UTS E		24 VIEWED	8 CAMERAS RECORDING	SD CARD SLOT	CODES	7" COLORS DISPLAY	CAPACITIVE TOUCH SCREEN	VOICE SYNTHESIS	USB PORT	32 PROGRAMS MANAGED
	Compatible systems: TP10-42 - TP8-88 - TP20-440 Touch screen video console for the integration of Videoalarm IP into the burglar alarm systems from Tecnoalarm The console permits the connection of up to 24 IP cameras via Ethernet. The cameras can be associated to the zones of the alarm system. The live streams of the cameras can be viewed in sequence (full screen mode) or on mosaics (showing 4 live streams simultaneously), both automatically or manually. The console is able to record video clips of 30s length for 8 of the 24 cameras. SD card slot - USB port - Stylish design - Ultra-thin casing - Surface and flush mounting - White cover plate (exchangeable) Three models are available according to the type of connection and power supply									
	The console is always equipped with the floor plan management function.								32 FLOOR PLANS	32 ICONS

UTS E POE		IP PORT POE	RJ45 INTERFACE	UTP CAT5 CONNECTION	POWER SUPPLY POE 48V	MAX CONNECTION DISTANCE 80m
	IP POE (Power over Ethernet) connection for data transmission and power supply - UTP CAT 5 - RJ45 - Max. connection distance 80m Item no. F210UTSEPOE					
UTS E IDC		IP PORT	IDC 110 INTERFACE	UTP CAT5 AND POWER CONNECTION	POWER SUPPLY 12V	MAX CONNECTION DISTANCE 80m
	IP connection for data transmission - Separate power cord - UTP CAT 5 - IDC 110 - Max. connection distance 80m Item no. F210UTSEIDC					
UTS E		IP PORT	RJ45 INTERFACE	UTP CAT5 AND POWER CONNECTION	POWER SUPPLY 12V	MAX CONNECTION DISTANCE 80m
	IP connection for data transmission - Separate power cord - UTP CAT 5 - RJ45 - Max. connection distance 80m Item no. F210UTSE					

UTS E - Accessories

	Item no. F127UTSECGM Silver gray cover plate
	Item no. F127UTSECG Titanium gray cover plate
	Item no. F127UTSECN Black cover plate
	Flush mounting box - Dimensions (L x H x D) 195 x 147 x 35mm
	Item no. C210INCASSOUTS