

Outdoor keypads

DIGITEX	 Approved for certified systems EN 50131  CODES  4 PROGRAMS MANAGED  CAPACITIVE TOUCH  VANDAL PROOF  CLASS IV GENERAL OUTDOOR  IP65
	Outdoor keypad with touch-sensitive steal membrane - Grazing keypad light generated by LED light strips - Management of 4 programs - RS485 connection - Surface mounting - Waterproof and vandal-proof aluminum die cast casing - Design by Pininfarina - IP65 - To guarantee water tightness, the console comes with 6 meters pre-wired cable - Dimensions (L x H x D) 81 x 121 x 24mm - Varnished aluminum - EN 50131 (approved for use with certified systems)
	Item no. F103DIGITEX

DIGITEX - Technical and functional specifications

General features	Type	DIGITEX	Anti-tamper protection	Anti-opening and anti-detachment	Magnetic - reed switch
	Address programming	Digital		Anti-magnete	Magnetic - reed switch
	Connection	RS485			
User interface	Keypad	Touch-sensitive steal membrane	Physical specifications	Connection cable	6m pre-wired
	Optical system status signaling	7 LED		Environmental class	IV
	Acoustic system status signaling	Buzzer		Protection class	IP65
	Keypad light	LED light strips - Grazing light		Casing	Al
				Dimensions (L x H x D)	81 x 121 x 24mm
				Weight	510g
Electrical specifications	Rated voltage	12V DC	Conformity	Standards	EN 50131-1* EN 50131-3*
	Operating voltage	10V...15V DC		Notified body	IMQ
	Stand-by consumption	10mA @ 12V DC			
	Max. consumption	136mA @ 12V DC			
Mechanical protection	Casing	Vandal-proof	*Certified only if combined with approved systems		

*Certified only if combined with approved systems