

UTS 4.3 PROX	 Approved for certified systems EN 50131	 CODES	 RFID READER	 COLOR DISPLAY 4.3"	 CAPACITIVE TOUCH SCREEN	 VOICE SYNTHESIS	 15 PROGRAMS MANAGED
	Console with integrated RFID reader and a multifunctional user interface composed of: TFT 4.3" capacitive touch screen, voice synthesis function (connection of S wire from the control panel required), acoustic signaling device and an interactive and intuitive graphic interface with icons contextual to the system status. Graphic help function - Management of 15 programs - RS485 connection - Stylish design - Ultra-thin ASA casing - Surface mounting - EN 50131 (approved for use with certified systems)						
	Item no. F127UTS43PROX (white)						
	Item no. F127UTS43PROXGR (charcoal gray)						

UTS 4.3 PROX - Technical and functional specifications

General features	Type	UTS 4.3 PROX	Electrical specifications	Operating voltage	10V...15V DC
	RFID reader	Integrated		Stand-by consumption	80mA @ 12V DC
	Connection	RS485		Max. consumption	160mA @ 12V DC
User interface	Screen	Color 4.3" TFT	Physical specifications	Environmental class	II
	Resolution	480 x 272 pixel		Protection class	IP4x
	Touch screen	Capacitive		Casing	ASA
	Infographics	Icons contextual to system status		Dimensions (L x H x D)	154 x 104.6 x 23mm
	Voice synthesis	✓		Weight	230g
	Speaker	✓	Conformity	Standards	EN 50131-1* EN 50131-3*
	Help function	Graphic		Notified body	IMQ
Anti-tamper protection	Anti-opening and anti-detachment	Micro-switch	<i>*Certified only if combined with approved systems</i>		