

INDOOR

Receivers

RX330					
	Wireless receiver module - Highly sensitive UHF receiver - 433/868MHz frequency bands - OOK modulation - ASYNC@WL protocol - Number of managed devices depends on system - RS485 connection - Programmable baud rate - Anti-tamper protection: anti-opening/antidetachment, antijamming - Environmental class II (indoor general) - ABS casing - Design by Pininfarina - White				
	Item no. F102RX330				

RX330 - Technical and functional specifications

General features	Type	RX330	Anti-tamper protection	Anti-opening	Micro-switch
	Connection	Serial Bus		Serial bus sabotage	✓
Wireless specifications	Communication protocol	ASYNC@WL	Physical specifications	Antijamming	✓
	Receiver	UHF		Environmental class	II
	Frequency bands	433/868MHz		Protection class	IP3x
	Modulation	OOK		Casing	ABS
Electrical specifications	Operating voltage	10V...14.5V DC		Dimensions (L x H x D)	270 x 156 x 68mm
	Consumption	42mA @ 12V DC		Weight	550g

Control units

TX240-3					
	Wireless key - 433MHz or 868MHz frequency band - ASYNC@WL protocol - 3 function keys - Function programmable: program and/or remote control management, panic alarm - Programmable attributes - Lithium battery included - Design by Pininfarina				
	TX240-3/433	Item no. F102TX240-3/433 - 433MHz frequency band			
	TX240-3/868	Item no. F102TX240-3/868 - 868MHz frequency band			

TX240-3 - Technical and functional specifications

General features	Type	TX240-3/433 TX240-3/868	Programmable functions	Program management	✓
	Function keys	3		Remote control management	✓
User interface	Signal LED	1		Operational attributes	✓
	Communication protocol	ASYNC@WL	Electrical specifications	Lithium battery	CR2032 - 3V
Wireless specifications	Transmitter	UHF		Battery autonomy	> 1 year
	Frequency bands	433MHz or 868MHz	Physical specifications	Casing	ABS
	Modulation	OOK		Dimensions (L x H x D)	65 x 40 x 15.5mm
				Weight	46g