

Transmitters

	TX310 TX310 M				
	Radio transmitter for indoor use, 2 inputs, dual transmission code, double transmission frequency 433/868 MHz. Additional input for external device: contact, rope contact or inertial. Self protected from opening and removal. Lithium power supply battery supplied. Surface Mount. Antistatic ABS enclosure. Dimensions [LxHxD] 114.5x38.5x30mm. White or brown.				
	Item no. F102TX310 (white) / ATA502				
	Item no. F102TX310/M (brown)				

TX310 - TX310M - Accessories

	BATTERY TESTER
	Tester to check the charge level of the TX310 transmitter battery.
	Item no. F102BATTERYTEST

Passive infrared for indoor use

	TWINBAND WL		Volumetric detectors for indoor use, 433/868 MHz dual transmission radio frequency. Range and coverage pattern differentiated on the basis of the protection models: volumetric, long range, curtain, volumetric for animals (see illustration of icons). Lithium power supply battery supplied.				
	TWINBAND WL/V						
	Item no. F102TWINBAND/V						
	TWINBAND WL/C						
	Item no. F102TWINBAND/C						
	TWINBAND WL/T						
	Item no. F102TWINBAND/T						
	TWINBAND WL/PET						
	Item no. F102TWINBAND/PE						

TWINBAND WL - Accessories

	SNODO 2000
	Self-protected swivel mounting bracket, orientation, +/-45° horizontal -15° vertical.
	Item no. F102SNOD02000 /ATA911