

Bus sirens for indoor use

SIRTEC BUS								
	Self-powered magneto-dynamic siren - Sound level 117dB(A) @ 1m - Numerous programming options for diversification of signaling according to the event - Free program association - Signaling for arming/disarming of the system - Self test function and failure signaling for: power supply, battery or horn failure - Integrated RSC® technology: remote programming and management - Anti-tamper protection: anti-opening/antidetachment - Environmental class II (indoor general) - ABS casing - Design by Pininfarina - EN 50131-4 certification security grade 3							
	Item no. F105SIRTECBUS (white)							
	Item no. F105SIRTECBUSGR (silver gray)							

SIRTEC BUS - Technical and functional specifications

General features	Type	SIRTEC BUS	Electrical specifications	Operating voltage	10.5V...14.5V DC
	Connection	Siren Bus		Stand-by consumption	8mA @13V DC
Acoustic features	Sound level	117dB(A) @ 1m		Max. consumption	1.8A @ 13V DC
	Frequency	2400Hz...3500Hz		Battery	12V/2Ah
Programmable functions	Program association	Programmable	Physical specifications	Environmental class	II
	Functioning mode	indoor or outdoor		Protection class	IP41-IPK07
	Volume adjustment	4 levels		Casing	ABS
	Sound type	3 modes		Dimensions (L x H x D)	290 x 95 x 70mm
	Signaling managed	Alarm Technical alarm Prealarm Arming/disarming Chime		Weight	780g
Anti-tamper protection	Anti-opening/detachment	Micro-switch	Conformity	Standards	EN 50131-4
Functions	Self test	Automatic		Security grade	3
				Notified body	IMQ