

SIRTEC	      
	Self-powered magneto-dynamic siren - Sound level 117dB(A) @ 1m - Frequency 2400-3500Hz - Programmable sound type and alarm time - Anti-tamper protection: anti-opening/antidetachment - Environmental class II (indoor general) - ABS casing - Design by Pininfarina - EN 50131-4 certification security grade 2
	Item no. F105SIRTEC (white)
	Item no. F105SIRTECGR (silver gray)

SIRTEC - Technical and functional specifications

General features	Type	SIRTEC			
Acoustic features	Sound level	117dB(A) @ 1m	Physical specifications	Environmental class	II
	Frequency	2400Hz...3500Hz		Protection class	IP41-1K07
Programming functions	Sound type	2 settings		Casing	ABS
	Power supply control	✓		Dimensions (L x H x D)	290 x 95 x 70mm
Inputs	Siren control	✓		Weight (w/o battery)	760g
Anti-tamper protection	Anti-opening/antidetachment	Micro-switch	Conformity	Standard	EN 50131-4
Electrical specifications	Operating voltage	10.5V...14.5V DC		Security grade	2
	Stand-by consumption	8mA @13V DC		Notified body	IMQ
	Max. consumption	1.8A @ 13V DC			
	Battery	12V/2Ah			