

Active infrared for outdoor use

DUALBEAM WL	Active radio infrared barrier, dual transmission frequency 433/868 MHz. DUALBEAM/WL provides an effective perimeter protection. Equipped with 2 protection beams, can cover a range of 80 meters. Lithium power supply battery supplied. ABS enclosure.
	433MHz TWIN 868MHz LITHIUM BATTERY POWERED TX + RX 2 BEAMS RANGE 80m IP52 Item no. F102DUALBEAMWL /ATA920
DUALBEAM HE WL	Active infrared wireless barrier, with radio and optical characteristics identical to the model DUALBEAM WL. The barrier DUALBEAM HE WL is equipped with a heater module and Ni-Cd rechargeable batteries. The power supply of the product must be provided by an external source. The power required is 18V AC 18W or 24V DC 600mA. Power data refer to a specific device, to supply the pair TX+RX it is necessary to double the current values.
	433MHz TWIN 868MHz Ni - Cd BATTERY POWERED TX + RX 2 BEAMS RANGE 80m IP52 Item no. F102DUALBEAMWLH

DUALBEAM WL - Accessories

	POST Post in galvanized sheet metal for the support of DUALBEAM and QUADBEAM barriers. Height 1,500 mm. Diameter 50 mm. Item no. F102PALOBEAM		POST MOUNTING KIT Post-mounting kit (50mm diameter) for barriers DUALBEAM WL and QUADBEAM. The kit includes the material necessary to fasten a pair of barriers (RX+TX). Item no. F102KITPALOBEAM
	MONITOR 868 Radio tester. The tester allows to test the alignment of: DUALBEAM WL, QUADBEAM, BEAMTOWER and EXPLORER BUS. Item no. F102MONITOR868		SHUTTERS Adjustable shutters for the alignment of: DUALBEAM WL, QUADBEAM and BEAMTOWER. The package contains 10 items. Item no. F102KITATTENUA
			OPTICAL VIEWFINDER KIT Alignment kit briefcase. Composed of optical viewfinder and 2 shutters for the alignment of: DUALBEAM WL, QUADBEAM and BEAMTOWER. Item no. F102KITMIRINO

Siren for outdoor use

SAEL 2000 WL Plastic cover (ASA) White	433MHz TWIN 868MHz TX BDI RX LITHIUM BATTERY POWERED XENON ASA BOX IP43								
	<table><tr><td>Compatibility</td><td></td><td>TP8-28</td><td>TP8-28 GSM</td><td>TP8-88</td><td>TP8-96 VIDEO</td><td>TP16-256</td><td>TP16-512</td></tr></table> Two-way radio siren, dual frequency 433/868 MHz. Self-powered for outdoor use. Self protected from opening and removal. Xenon flashing light. Sound power 117dB(A) at 1m. Lithium power supply battery supplied. Design by Pininfarina. Base ABS enclosure, ASA cover. White. Dimensions (LxHxD) 211x315x98mm.	Compatibility		TP8-28	TP8-28 GSM	TP8-88	TP8-96 VIDEO	TP16-256	TP16-512
Compatibility		TP8-28	TP8-28 GSM	TP8-88	TP8-96 VIDEO	TP16-256	TP16-512		
	Item no. F105SAEL2000WL (White) /ATA601								