

INDOOR

EV IRSPACE BWL							
	2-way wireless passive infrared detector - Volumetric protection: 28 infrared beams, 4 circles, 360° coverage, 5m maximum range - Programmable pulse count - Integrated RSC® technology: remote programming and management - Anti-tamper protection: anti-opening/antidetachment, supervision - Lithium battery included - Surface ceiling mount - Environmental class II (indoor general) - ASA casing - White						
	Item no. F102EVIRSPACBWL						

EV IRSPACE BWL - Technical and functional specifications

General features	Type	EV IRSPACE BWL
Detection features	Infrared detector	Dual PIR element
	Infrared beams	28
	Levels (infrared beams)	4
	Coverage	H 360°, V 99°, 5m range
	Pulse count	Programmable
Wireless features	Communication protocol	EV@BWL
	Transmitter-receiver	UHF
	Frequency band	868MHz
	Modulation	FSK
Anti-tamper protection	Anti-opening and anti-detachment	Micro-switch
	Supervision	✓

Electrical specifications	Lithium battery	SOCL2 - 3.6V
	Battery life	> 4 years
Physical specifications	Environmental class	II
	Protection class	IP4x-IK04
	Casing	ASA
	Dimensions (Ø x H)	104 x 40mm
	Weight	175g
Conformity	Standards	EN 50131-1 EN 50131-2-2 EN 50131-5-3
	Security grade	2
	Certification	Pending

Coverage diagrams

