


Chain Actuator EA-KSV-24/250/300

This modern 24 V chain actuator offers all comfort for a remote controlled operation of windows.

The compact housing in shapely design and the progressive technology are outstanding characteristics for ventilation applications.

The actuator has a practical and user friendly mounting bracket that is simple to install. Also available in 230 V version (see 230 V actuators).



Brackets to be ordered separately!

Technical Data:

Chain actuator Type EA-KSV-24/250/300	
Nominal voltage (min./max.):	24 VDC (± 10 %)
Nominal current:	0.7 A
Stroke length:	300 mm
Force:	250 N
Cut-off:	Electrical
Speed:	9 mm/s
Dimensions (LxWxH):	Capsuled aluminium-diecast box, powder-coated RAL 9006 450 x 45 x 32 mm
Ingress protection:	IP 30
Switch on duration:	ED 50 %
Temperature range:	- 5° up to + 65° C
Connection cable:	Synthetic cable, white, length 1.5 m
Weight:	Approx. 1.4 kg

Brackets Type K-KS

Bracket type K-KS-D32 Consisting of 2 sliding pieces with stud bolts, 2 fixing brackets and 1 movable mounting angle, powder coated in RAL 9006. Bracket type K-KS-D80 Consisting of 2 sliding pieces with stud bolts, 2 fixing brackets, powder coated in RAL 9006. Bracket set type K-KS-D15 Pivotal mounting bracket consisting of 2 fixing brackets incl. stud bolts and nuts, Width 15 mm, colour RAL 9006.

Accessories	Item number
K-KS-D15 Length 15 mm	K2 5073
K-KS-D32 Length 32 mm	K2 5071
K-KS-D80 Length 80 mm	K2 5072
K-KS-SKI-V5 Mounting angle for inward opening windows	K2 5076
K-KSV-D55	K2 5082