

De oplossing voor uw tijdopvolgingsproblemen
dankzij de

prikklok met proximitylezer ACC482

La solution pour tous vos problèmes de gestion de
temps grâce à la

pointeuse à lecteur à proximité ACC482



Technical Specifications

- **Card Holders:** 30.000 cards
- **Transaction Capacity:** 50.000 records
- **CPU:** 64bit Microprocessor
- **Hardware:** ZEM500 (Embedded Linux O/S)
- **Access Mode:** Card Only, PIN Only, Card+PIN
- **Read Range:** 10-15 cm
- **I/O Interface:** RS232 (10m) / 485 (1.2km)
- **Baud Rate:** 9600-115Kbps programmable
- **Ethernet:** 10/100M
- **Wiegand I/O:** any bit
- **USB:** Mini-USB 2.0 port
- **Access Control Function:** 50 time zones, 5 groups, 10 open door combination, supports multi-users enter. TTL for connecting to lock, door sensor, exit button, alarm
- **LCD Panel:** 4 line, 16 character each line (User name, ID number, time, date, states)
- **Keypad:** 4x4 metal keypad with 4 function keys
- **Audio Visual Indicator:** Red LED (Access denied) / Green LED (Access granted) with Audible Beep
- **Housing Material:** ABS
- **Power Requirement:** 12V DC, 400mA
- **Operating Temperature:** 0°C-45°C **Operating Humidity:** 20%-80% - indoor use
- **Options:** Webserver, Antipass-back, Multi-language display.