

Network Range Mini Double Technology - BIOPROX-EH



NEW!

BIOPROX-EH & BIOPROX-MF

Small metal biometric and proximity reader with large rectangle shaped status LED.



MCD-MINI

Compulsory protection cover supplied with reader for external use.



BIOPROX-EH

Montage: Housing: Colour: Technology: Identification: Resin potted electronic: Proximity reading type: Distance de lecture: Communication Protocols: Protocol Programming: Type of biometric sensor: Identification: Fingerprint Enrolment: Fingerprints number stored: Wiring: Green & Red LED: Orange LED: Buzzer: Consumption: Power Supply: IP Rating: Operating Temperature: Dimensions (mm):

Surface Moulded Aluminium Light Grey, Green, Dark Grey, Red, Blue and White Biometry & proximity Finger, Card, Finger or/and Card Yes EM 4002/EM 4100 and HID (125Khz) 2 à 5cm Wiegand 8 to 128 bits By PROS software (EWS system) & BIOMANA-GER CS (All Access Control Systems) Capacitive < 1 sec On the reader or from the enrolment desktop reader USB (BIOE) 9500 1m Externally Controlled Programming Status Yes 90mA Max 12V CC 65 -20°C to +50°C 100 x 94 x 30

EM & HID
125Khz
Compatible

MIFARE



Ref.	BIOPROXS-EH	BIOPROXC-EH	BIOPROXB-EH	BIOPROXG-EH	BIOPROXR-EH	BIOPROXW-EH
Colour	Silver	Charcoal	Blue	Green	Red	White
Ref.	BIOPROXS-MF	BIOPROXC-MF	BIOPROXB-MF	BIOPROXG-MF	BIOPROXR-MF	BIOPROXW-MF
Colour	Silver	Charcoal	Blue	Green	Red	White
	ACC870	ACC867	ACC866	ACC868	ACC869	ACC871