

Network Range Mini Flush mount Range



DINPAD-M



Mounting: **DIN Flush Mount**
 Housing: **ABS**
 Keys: **Backlit Metallic**
 Communication Protocols: **Compatible with WIEGAND 26, 30, 34, 40bit, Clock & Data or Codix**
 Slave devices: **DINMTPX-M, DINMTPX-MF**
 Green LED: **Free tension**
 Red LED: **Free tension**
 Orange LED: **Programming Status**
 Buzzer: **1**
 Antitamper protection: **When Opened or Dismantled**
 Wiring: **Terminal block**
 Consumption: **Max. 70 mA**
 Power: **9-14V DC**
 Illumination: **Blue backlight (ON/OFF)**
 IP Rating: **40**
 Operating Temperature: **-20°C to +50°C**
 Dimensions (mm): **70x70x9**

Choose the finish product:

			
Ref.	DINPADS-M	DINPADC-M	DINPADB-M
Features	Silver	Charcoal	Blue

			
Ref.	DINPADG-M	DINPADR-M	DINPADW-M
Features	Green	Red	White

DINMTPX-M



Mounting: **DIN Flush Mount**
 Housing: **ABS**
 Communication Protocols: **Wiegand 26 or 34 bits (jumper selection)**
 Proximity reading type: **EM4100**
 Reading distance: **max. 8cm**
 Wiring: **terminal block**
 Power Supply: **9-14V DC**
 Green LED: **Potential Free**
 Red LED: **Potential Free**
 Orange LED: **Communication status**
 Antitamper Protection: **When opened or dismantled**
 Buzzer: **1**
 Consumption: **max. 45mA**
 IP Rating: **40**
 Operating Temperature: **-20°C to +50°C**
 Dimensions (mm): **70x70x9**



Choose the finish product:

						
Ref.	DINMTPXS-M	DINMTPXC-M	DINMTPXB-M	DINMTPXG-M	DINMTPXR-M	DINMTPXW-M
Features	Silver	Charcoal	Blue	Green	Red	White
	EM4100					

DINMTPX-MF

Mounting: **DIN Flush Mount**
 Housing: **ABS**
 Communication Protocols: **Wiegand 26 or 34 bits (jumper selection)**
 Proximity reading type: **Mifare Classic, Mifare Ultralight, Mifare Desfire (13, 56MHz)**
 Reading distance: **max. 8cm**
 Wiring: **terminal block**
 Power Supply: **9-14V DC**
 Green LED: **Potential Free**
 Red LED: **Potential Free**
 Orange LED: **Communication status**
 Antitamper Protection: **When opened or dismantled**
 Buzzer: **1**
 Consumption: **max. 150mA**
 IP Rating: **40**
 Operating Temperature: **-20°C to +50°C**
 Dimensions (mm): **70x70x9**



						
Ref.	DINMTPXS-MF	DINMTPXC-MF	DINMTPXB-MF	DINMTPXG-MF	DINMTPXR-MF	DINMTPXW-MF
Features	Silver	Charcoal	Blue	Green	Red	White
	Mifare Classic, Mifare Ultralight, Mifare Desfire (13, 56MHz)					