


iZero

Petit par sa taille,
grand par ses performances




6,5 cm

10 cm



3,5 cm

- Discrète
- Autonôme
- Performante



Le système iZero est une solution élégante pour les entreprises, parkings, hôtels, campings, appartements et villas.

Réf. PRK520 / PRK 520-WG

iZeroTM


Une caméra discrète de grande précision

CAMERA
COMPACTE

H = 10 cm

L = 6,5 cm

P = 3,5 cm



Découvrez les performances exceptionnelles de l'iZero.

Sa caméra 2MP lit aussi bien les plaques d'immatriculation de camions, de voitures et de motos avec une précision de reconnaissance pouvant atteindre 99,8 %. Intégrée dans une colonne en aluminium, l'iZero est facile à installer et à configurer. En plus, il est compatible avec les systèmes de contrôles d'accès les plus courants tels que XPR, Siemens, Honeywell, HID, ...

ANPR-OCR



IN-OUT

PRECISION
DE RECONNAISSANCE

99,8%

INTERFACES:

Rs232-485

OSDP


Wiegand

CONNECTEUR USB:




Wifi

STOCKAGE




JUSQU'À

1TB



RELAY

1A - 30 VDC



POE


802.3AF



COLONNE
EN ALUMINIUM

Caractéristiques principaux

- Portée de lecture : de 1,5 m à 4 m
- Entrée de commande
- Contact relais standard
- Emplacement mémoire MicroSD
- Interfaces disponibles : RS232/485, Wiegand, OSDP, TCP/IP
- Connecteur USB (PRK520-WG): Wifi / stockage supplémentaire (jusqu'à 1 To)
- Choix d'alimentation : 220Vac / 12 Volt ou standard P.O.E.
- Système d'exploitation : Linux (mises à jour régulières)
- Boîtier autonome en aluminium (500x83x88 mm)
- IP66



Disponible en 2 versions :

	PRK520	PRK520-WG
2 entrées opto-isolées	•	•
1 sorties opto-isolé	•	•
1 relais de sortie	•	•
Alimentation par Ethernet standard 802.3af		•
Interface RS232		•
Interface WIEGAND		•
Interface semi- duplex RS485		•
Mémoire interne 16 GB		•
Connecteur USB pour WIFI / stockage supplémentaire 1TB		•



Description	PRK520	PRK520-WG
OCR CAMERA		
Sensor	Global Shutter CMOS - 54 Fps - high speed - B/N	
Resolution	2 Megapixel	
Plate reading lens	Fixed focal 3.6 mm with M12 coupling	
PLATE READING		
Plate reading OCR	Integrated on board	
Reading timing	Automatic (free flow) without the aid of equipment or trigger	
Character sets	Latin alphabet: plates from Europe, Canada, Turkey, Nigeria, South Africa and many more	
Syntax and nationalities (syntax free mode)	No syntax and nationality limits, with the exception of the set of national characters that the OCR knows how to recognize (the OCR can be instructed on other character sets). No library constraint.	
Recognition of nationality	The camera can identify the vehicle nationality and creates black/white lists for both italian and foreign vehicles, from specific Countries.	
Syntax filter	The camera can operate both with the syntax entered and without using syntax (syntax free).	
Type of vehicles recognized	Optimized OCR for reading repeating plates on trucks, cars, heavy goods vehicles, Law Enforcement vehicles, Ambulances and military vehicles, motorcycles and motorbikes.	
Type of plates readed	Both front and rear vehicle plates	
Type of ADR readed	Both front and rear plates, front ones suggested.	
Precision	Up to 99,8% with the vehicle stationary	
Field depth	From 1,5 to 4 m	
Gate width	3,5 m (single lane)	
Speed of plate reading (free flow)	vehicle stationary	
IR BEACON		
IR leds	N.6 IR leds - High power	
Type of beacon	Pulsed illuminator able to adapt power to the conditions of reflectance and lighting in the environment.	
Exposure mode	Multi-exposure	
Optimal beacon distance	2 ~ 3 m	
Max beacon distance	5 m	



Description	PRK520	PRK520-WG
INTEGRATED ALGORITHMS		
MAGIC SPOT®: this algorithm makes the plate area visible even when the photographic image is illegible to the human eye.		
Dirt cleanup effect: to avoid reading issues caused by external elements as snow, dirt, dust, bugs...		
Video analysis: permits selecting the best image among those took by the multiple exposures.		
Perspective compensation: allowing readings on very angulated images		
Symbols removal effect: any symbol, patch, ads, label or tag		
Predictive character analysis algorithm, probabilistic-based, to improve the reading accuracy.		
EMBEDDED FEATURES		
The camera embedded the following main features:		
◦ Double FTP server and dual TCP / IP server ◦ Dynamic customizing of FTP notifications ◦ Customizing TCP notification that allows to integrate the camera in all CPS servers ◦ Management of multiple users with access credentials and protected HTTP protocol to access the camera ◦ Management of lists (white / black, no list) with alarm functionality ◦ Synchronized saving of metadata, code/ number plate image and contextual images ◦ Integration and saving of context images from external IP cameras (<i>FULL version</i>) ◦ Privacy management with auto deletion of data and images after a certain time period ◦ Statistical analysis useful for security and traffic analysis ◦ Plate, date / time searches, even through the use of logical expressions for partial code / number plate search ◦ Notifications (codes / plate) and researches export in CSV format ◦ Integration with third-party VMS solutions ◦ Record on local or remote NAS server ◦ Security management via HTTPS standard ◦ FTP security management with FTPS over TLS / SSL protocol ◦ Protected email sending management over TLS / SSL protocol ◦ Alarm management with multiple actions ◦ Live and check control feature (Live, CPS, FTP, VPN) on system functioning ◦ Possibility of firmware updates via web page		
INTERNAL STORAGE		
Embedded Hard Disk	Not included	16 GB micro SD standard
White/Black lists	can store an unlimited quantity of lists	
Storage management	Automatic: image auto-deleting (FIFO method).	
OUTPUT VIDEO		
Video format	Mpeg4, H264.	
Video conformity	RTP/RTSP Onvif S profile	
OCR reading image format	Jpeg	



Description	PRK520	PRK520-WG
DATA and I/O INTERFACE		
Data transmission interface	n.1 gate 10/ 100 Mbps Ethernet/IEEE standard 802.3	
Communication interface	Not included	RS232, RS485 half duplex, Wiegand, OSDP
Camera access mode	The cameras have an integrated web-server. Allows for direct viewing of the images, memory access and configuration through the browser.	
Transmission mode (protocols)	TCP/IP, UDP, HTTP, HTTPS, FTP, FTPS, RTP/RTSP, DHCP	
Input	N.2 digital inputs	
Output	N.1 digital output N.1 clean contact - relay 1A - 30 Vdc	
PROTECTIONS		
Data ports	TVS protections on USB and Ethernet ports	
Power	Anti-inversion protection on the power supply Protection against overvoltage transient over 17V	
Temperature	Power switching with Thermal Shutdown Protection	
Consumptions	Power Save Mode	
GENERAL		
Operating system	Linux embedded	
Updates and maintenance	Selea owns 100% of the knowledge and intellectual property of the product, assuring regular updates to the customers	
Integration	The device integrates with the most known video management and video surveillance management platforms, as Genetec, Milestone, Tyco...	
Operating temperature	From -25°C to +45°C	
Power supply	• 12 Volt dc $\pm 10\%$	• 12 Volt dc • P.O.E standard 802.3af
Absorbed power	230 Vac $\pm 10\%$ (optonal power supply for both versions)	
Column dimensions (in mm)	8 Watt max	
Weight	L=83 : H=500; P=88	
Type of housing	1,8 Kg	
Protection rating	Die-cast aluminium	
	IP66	