

Standalone Range Wiegand Standalone Controller and Biometric Standalone Controller



SC24000

The standalone Wiegand controller

New



DINPAD-M, MTPAD-M, INOX, VKP and LCS



LCSP, LCSP-MF, MINI-M, MINI-MF, MTPX-M, DINMTPX-M, DINMTPX-MF and VPROX-2M



This controller can be combined with the following readers.

EX8-43B

The standalone biometric controller



This controller can be combined with the BIOC biometric reader.



Ref.	SC24000	SC24000-E
Features	- Electronic and DIN rail enclosure - Auto detect Wiegand 26 Wiegand 34 - For Wiegand proximity readers and keypads	- Electronic only - Auto detect Wiegand 26 Wiegand 34 - For Wiegand proximity readers and keypads

Ref.	EX8-43B	Ref.	BIOC2S-SET	BIOC2C-SET	BIOC2B-SET	BIOC2G-SET	BIOC2R-SET	BIOC2W-SET
Features	Standalone biometric controller Wiegand 26 bits + RS485 For biometric readers	Features	BIOC in Silver color provided with EX8-43B	BIOC in Charcoal color provided with EX8-43B	BIOC in Blue color provided with EX8-43B	BIOC in Green color provided with EX8-43B	BIOC in Red color provided with EX8-43B	BIOC in White color provided with EX8-43B

