

Network Range Biometric Readers



BIOC2

*Stylish network biometry readers
with Wiegand output.*



Mounting: **Surface**
 Housing: **Moulded Aluminium**
 Colour: **Light Grey, Green, Dark Grey, Red, Blue and White**
 Technology: **Biometry**
 Communication Protocols: **Wiegand 8 to 128 Bits**
 Protocol Programming: **By PROS software (EWS system) & BIOMANAGER (All Access Control Systems)**
 Type of biometric sensor: **Capacitive**
 Identification: **<1sec**
 Fingerprint Enrolment: **On the reader or from the enrolment desktop reader USB BIOE (Software PRO or BIO-MANAGER + Compulsory Converters CNV-100/200 or 300)**
 Fingerprints number stored: **9500**
 Wiring: **Terminal Blocks**
 Power Supply: **12 VDC**
 Green & Red LED: **1 Potential Free**
 Orange LED: **Communication Status**
 Buzzer: **With intensity (programming)**
 Consumption: **200mA Max**
 IP Rating: **54 (internal use only)**
 Operating Temperature: **0°C to +40°C**
 Dimensions (mm): **92x51x25**



						
Ref.	BIOC2S	BIOC2C	BIOC2B	BIOC2G	BIOC2R	BIOC2W
Colour	Silver	Charcoal	Blue	Green	Red	White