

Aluminum Dome Camera



Aluminum Dome Camera
AU-HLC542X

Features

- Sony 1/3" CCD 540 TVL High Resolution CCD
- Minimum illumination: 0 Lux (with IR LED ON)

Specification

Pick Up Element	SONY 1/3" CCD
Effective Picture Elements (H*V)	NTSC: 811x508, PAL: 795x596
Horizontal Resolution	540 TV Lines
S/N Ratio	More than 48dB
Clock Frequency (MHZ)	NTSC: 19.0699, PAL: 19.3125
Scanning System	2:1 interlace
Minimum Illumination	0 Lux. (with IR LED ON)
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	NTSC: 1/60s ~ 1/100.100s PAL: 1/50s ~ 1/100.000s
Gamma Characteristic	0.45
IR Project Distance	30 Meters (with 36 Unit Infrared LED)
IR Status	Under 10 Lux. by CDS
Video Output	1Vpp, 75Ω
Auto Gain Control	Auto
Power / Current	12VDC(+/-10%) / 400mA
Lens	3-9 mm
Dimension (mm)	Φ 94x68.5(H)
Weight (g)	580
Storage Temperature	-30 ~ +60°C
Operating Temperature	-10 ~ +45°C

Technical spec are subject to change without prior notice. The product may appear different as picture above.