



- Powerful 10x/12x optical zoom
- High resolution@700TVL/600TVL
- WDR(DWDR),Day/Night(ICR),DNR(2D&3D)
Auto iris,Auto focus,AWB,AGC,BLC
- Max300°/s pan speed,360°continuous pan rotation
- Up to 128 presets,4 auto scan,4 tour,4 pattern
- Power up Action,Idle Motion,Time Task support
- Support 4/2ch alarm in/out(Optional)
- 1500V Wave&surge protection,
Temperature:-10~50°C,DC12V
(Built-in Heater&fans,-40~60°C,is Optional)

Functional

Specifications

Download

Main Features

- High performance CCD, clear image
- Precision motordriven, sensitive response, stable operation, accuracy deviation is less than 0.1 degrees, jitter- free images at any speed
- Support automatic identification for Pelco-P / D protocol under control of RS-485
- Support for three-dimensional intelligent positioning function, click-tracking and amplification with the coordination of DVR and client software
- Support for multi-language menu and operation prompts, user-friendly interface
- Data will not be lost when the electricity is turned off
- Support memory function under outage, PTZ and lens automatically return to the former states when power is on.
- The temperature inside can be displayed with the built-in temperature sensor,
- Support for lightning protection, anti-surge
- Waterproof rate: IP66
- Supports 3DNR
- Support for regular tasks preset / pattern scan / cruise scan / horizontal scan / Vertical Scan / Random Scan / Frame Scan / panorama scanning function
- Timer start function, The dome automatically executed preset,cruise, area scan, pattern scan function at a set time without receiving control commands