


Dome Eye-ball



**2MP WDR VF Deep learning
Network IR Eyeball Camera**

UNV2510N

IPC3632SB-ADZK-10



security

by **nestor**
company

Focus on **expertise**,
supplier of **security**

Meer weten over ons compleet assortiment?

Contacteer uw vertegenwoordiger of
bezoek ons kenniscentrum.



nestor company

E3-laan 93 9800 Deinze - Tel. 32 (0)9 380 40 20
sales@nestorcompany.be - www.nestorcompany.be

specificaties

CAMERA					
Sensor	1/2.8" , 2.0 megapixel, progressieve scan, Cmos				
Lens	2.7 ~13.5 mm, AF automatische focus en gemotoriseerde zoom lens				
Gezichtshoek	H: 107.4° ~ 29.2°		V: 54.2° ~ 16.3°		O: 111.0° ~ 33.1°
Dori distance	Lens (mm)	Detectie (m)	Observer (m)	Herken (m)	Indentifieer (m)
	2.7	41.9	16.8	8.4	8.2
	13.5	209.5	83.8	41.9	20.9
Hoekverstelling	Pan: 0° ~ 360°		Tilt: 0° ~ 75°		Draai: 0° ~ 360°
Minimum verlichting	Kleur: 0,0005Lux (F1,2 - AGC on)			0 Lux met IR	
S/N	>52dB				
WDR	120dB				
IR bereik	Tot 40m bereik				
IR On/off control	Auto/manueel				
Shutter	Auto/manueel, 1 ~ 1/100000s				
Dag/Nacht	IR-cut filter met auto switch (ICR)				
Video compressie	Ultra 265 , H.265 , H.264 , MJPEG				
H.264 profiel code	Baseline profile , Main profile, High profile				
Frame rate	Main stream: 2MP (1920*1080), Max 30fps; 720P (1280*720), max 30fps Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; Third Stream: D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288),				
Video bit rate	128 Kbps ~ 16Mbps				
OSD / ROI	tot 8 areas				
Privacy mask Motion Detectie	tot 4 areas				
Smart IR / Flip / Dewarping / HLC / BLC / Defog	ondersteund				
NETWORK					
Protocols	IPv4, IGMP, ICMP, ARP, UDP, DHCP, PPPoE, RTP, TRSP, RTCP, DNS, DDNS, NTP, FTP, UPnp, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS				
Compactibele integratie	ONVIF (Profile S, Profile G, Profile T), API				
Netwerk	1 RJ45 10M/100M Base-Tx Ethernet				
Edge storage	Micro SD, tot 256 GB				
Network storage	ANR, NAS (NFS)				
Smart Intrusion Detection	Cross Line, Intrusion, Enter Area, Leave Area detection				
ALGEMEEN					
Voeding	DC 12V±25%, PoE (IEEE 802.3af) ; verbruik: max 7.0W				
Afmeting (Ø x H)	Ø 129 x 110 mm (Ø5.1" x 4.3")				
Netto gewicht	0.69kg (1.52lbs)				
Werkingsomgeving	-30°C ~ 60°C (-22°F ~ 140°F, vochtigheid <95%RH (niet condenserend)				
Audio I/O & Compressie	1/1, G711				
Veiligheid	Overspanning: 6KV		IP67		Vandalisme bestendig: IK10
Certificaten	CE: EN 60950-1		UL: UL60950-1		FCC: FCC Part 15

afmetingen



accessoires

UNVA008	UNVA010	UNVA015	GPUA001
Back box	Muur montage met outlet	Muur montage Eyeball zonder outlet	Paal montage



UNVA015

NPT 3/4" Plastic
Waterproof joint

