

AC-Q41SB

Anti-Vandal Slim Backlit PIN Standalone Controller

ref. Nestor: COD040



120 x 76 x 22 mm (4.72 x 3 x 0.85 in.)

water- en vandaalbestendig, IP65
ingebouwde verwarming tegen bevriezen
500 gebruikers
8-cijferige PIN-codes
ideaal voor high traffic omgevingen

- robuuste metalen constructie
- 2 relais (2 Amp)
- 3 operationele beveiligingsniveaus: normal, secure en master
- active led controle blauw backlight
- aantrekkelijk, slank design
- water- en vandaalbestendig
- IP65 tamper mogelijk (automatische desactivatie bij loshalen)
- kleuren led's voor makkelijke programmering
- gemakkelijke installatie
- 5 jaar garantie



nestor
company

SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

■ Operating Voltage Range	12 to 24 VDC, from a regulated power supply 12 to 24 VAC, from a transformer
■ Input Current	(Heater Off) Standby: 70 mA, Maximum: 130 mA, at 12 VDC (Heater On) Standby: 550 mA, Maximum: 610 mA, at 12 VDC
■ Relay Outputs	Lock Strike: 2A, N.O. and N.C. Auxiliary: 2A, N.O. and N.C.
■ Tamper	Optical back tamper sensor, O.C. active low 32 mA max sink current
■ Inputs	REX: N.O. Dry Contact Auxiliary (In/Monitor): N.O. Dry Contact, 10 programmable modes

OPERATIONAL SPECIFICATIONS

■ Capacity	500 users, single / dual code each
■ Keypad	3x4 Blue illuminated Keys for local programming and 4 to 8 digit PIN codes entry
■ User Levels	Normal, Secure, Master
■ Security Modes	Normal, Bypass, Secure
■ Audio/Visual	Interface for BL-D40 (bell, chime, and siren enunciator) Two tri-color LED indicators, built-in sounder
■ Design	Epoxy potted, fully sealed in a rugged metal enclosure, highly strong construction, blue backlit metallic keys. Suitable for extremely harsh environments

ENVIRONMENTAL SPECIFICATIONS

■ Operating Environment	Water resistant, suitable for outdoor use, IP65 rated
■ Operating Temperature	-20°C to 60°C (-4°F to 140°F). Built-in heater to prevent key freezing
■ Operating Humidity	0 to 95% (non-condensing)
■ RFI Protection	> 20 V/m up to 1000 MHz

PHYSICAL SPECIFICATIONS

■ Dimensions	120 x 76 x 22 mm (4.72 x 3 x 0.85 in.)
■ Weight	521 g (1.18 lbs)

SYSTEM COMPONENTS

The AC-Q41SB is compatible with the BL-D40 alarm, chime and door bell enunciator/strobe unit, as well as with the EX-06/16/07/17 Push to Exit buttons.

PRODUCT WARRANTY

5-year Limited Product Warranty

