

INOX99

Standalone vandal-proof keypad

Mullion and vandal-resistant access control keypad with metal keys for doorframe mounting. With user memory of 99 codes and one push button, **INOX99** is the best solution for single door access control. Photoelectric sensor for automatic illumination is effective in low-lit conditions. **INOX99** with a rugged good look is designed to operate even in harsh environments.

FEATURES

- : Standalone vandal-proof keypad with backlit metallic keys
- : Potted keypad in die-cast zinc alloy housing with 12-core cable
- : Indoor/outdoor installation
- : Photoelectric sensor automatically adjusts the backlighting
- : 99 User memory (codes up to 8 digit long)
- : 2 outputs, operate either in pulse (01 ... 99 sec) or latch mode
- : Tamper protection via in-built Reed Switch and magnet
- : One Request-to-exit button
- : Dipswitch for regaining the default settings
- : Invalid code lockout feature
- : Yellow LED and buzzer for programming and status indication
- : Green LED indicates relay activation and Red LED indicates transistor activation
- : EEPROM stores data, unaffected by power failure
- : Option available to connect peripherals using the 3-wire CODIX bus

SPECIFICATIONS

Electrical Characteristics :

Operating Voltage:	12/24V AC/DC
Current consumption:	Standby: 10 mA; Maximum: 60 mA
Outputs:	1 Relay(2A), 1 Transistor; Latch or Pulsed mode (01 to 99sec)
Keypad Lighting:	Backlit for 10 seconds for each press of keys
Visible Signals:	Yellow, Red and Green LED
Audible Signal:	One internal buzzer

Environmental Characteristics :

Operating Temperature:	-25°C to 70°C
Operating Humidity:	0 to 95% (non-condensing)

Mechanical Characteristics :

Dimensions (mm):	150 L x 50 W x 25 H
Cable:	1 m long, 12-core
Weight (g):	544



INOX99-B

INOX99-G

INOX99-C

PRODUCT REFERENCES

INOX99 is available in powder-coated white (**INOX99-B**) or grey (**INOX99-G**) or with MATT chrome finish die-cast zinc alloy housing (**INOX99-C**).

