

Typ Artikel Nr.	GE 125 TTLi 101115	GE 225 TKLL 101126	GE 245 TKLL 101146	GE 365 CKLL 101167	GE 499 TKLL 101270	Type Article No.	
Zulassungen	aktuelle Prüfzertifikate können angefordert werden					current test certification can be requestet	Licence
C-Profile:	AL 15-9	AL 25-14 AL 25-10V AL 25-10H	AL 25-14 AL 25-10H AL 25-10H	AL 35-14 AL 35-15HB	AL 35-14 AL 35-15HB	C-profile	
Material	TPE	EPDM	EPDM	EPDM	EPDM	Material	
Lieferränge	25 m	25 m	25 m	25 m	25 m	Delivery length	
Gewicht Kg/ m	0,2			1,25	1,9	Weight Kg/m	
Zubehör Anschlußstecker Abschlußstecker Endkappe Aufsatzpuffer	KS 3 L x.x m KS 3 W EK 125 TL AP 15-30	KS 6 L x.x m KS 6 W EK 225 TL AP 20-27	KS 6 L x.x m KS 6 W EK 245 TL AP 25-47	KS 6 L x.x m KS 6 W EK 365 TL AP 35-70	KS 6 L x.x m KS 6 W	Equipment Connecting Plug Terminal Plug End Cap Stopper	
Prüfung nach EN 1760-2, Geschwindigkeit 10 mm/s, Temp. 20°C, Prüfkörper rund Ø 80mm, Betätigungspunkt C3				Tested according EN 1760-2, Speed 10 mm/s, Temp. 20°C, Test Unit Ø 80mm round, Actuating Point C3			
Betätigungskraft F _A /N	27,3 N	64,1 N	69,1 N	78,2 N	82,6 N	Actuating Force F _A /N	
Ansprechweg S _B /mm	1,77 mm	4,7 mm	6,73 mm	5,16 mm	33,42 mm	Actuating Distance S _B /mm	
Nachlaufweg S _V /mm	10,47 mm	6,48 mm	20,75 mm	33,78	67,01 mm	Overtravel Distance S _V /mm	
Prüfung nach EN 1760-2, Geschwindigkeit 100 mm/s, Temp. 20°C, Prüfkörper rund Ø 80mm, Betätigungspunkt C3				Tested according EN 1760-2, Speed 100 mm/s, Temp. 20°C, Test Unit Ø 80mm round, Actuating Point C3			
Betätigungskraft F _A /N	33,0 N	70,9 N	81,2 N	107,7 N	107 N	Actuating Force F _A /N	
Ansprechweg S _B /mm	2,26 mm	5,0 mm	7,47 mm	6,23 mm	36,79 mm	Actuating Distance S _B /mm	
Nachlaufweg S _V /mm	10,04 mm	6,9 mm	20,51 mm	32,76 mm	64,46 mm	Overtravel Distance S _V /mm	