

1800 N

The compact range for light or glass doors

- Corrosion proof (ISO tested)
- No residual magnetism
- Built-in MOV surge protection
- 10 years warranty

iGEM 30S



Surface mount

Holding force	1 800 N (~400 lbs)
Voltage	12/24 VDC
Current	350/175 mA
Locking Monitoring	Reed contact
Door position Monitoring	no
Internal timer	no
Sizes: LxWxH	166 x 39 x 21
Weight	~ 1,8 kgs

iGEM 30M



Mortise mount

Holding force	1 800 N (~400 lbs)
Voltage	12/24 VDC
Current	350/175 mA
Locking Monitoring	Reed contact
Door position Monitoring	no
Internal timer	no
Sizes: LxWxH	143 x 34 x 24
Weight	~ 1,8 kgs

800 N

The mini range for specific applications, like box, fridge, ...

- Corrosion proof (ISO tested)
- No residual magnetism
- Built-in MOV surge protection
- 10 years warranty

iGEM 15S



Surface mount

Holding force	800 N (~180 lbs)
Voltage	12/24 VDC
Current	350/175 mA
Locking Monitoring	Reed contact
Door position Monitoring	no
Internal timer	no
Sizes: LxWxH	108 x 38 x 21
Weight	~ 0,5 kgs