

3000 N

The medium range for standard security doors

- **Corrosion proof (ISO tested)**
- **No residual magnetism**
- **Built-in MOV surge protection (Except EM1)**
- **10 years warranty**

iGEM 2H



Surface mount

Holding force	3 000 N (~670 lbs)
Voltage	12/24 VDC
Current	500/250 mA
Locking Monitoring	Led + Relay
Door position Monitoring	no
Internal timer	no
Sizes: LxWxH	268 x 48 x 25
Weight	~ 2 kgs

iGEM 1H



Surface mount

Holding force	3 000 N (~670 lbs)
Voltage	12/24 VDC
Current	500/250 mA
Locking Monitoring	no
Door position Monitoring	no
Internal timer	no
Sizes: LxWxH	268 x 48 x 25
Weight	~ 2 kgs

iGEM 2



Mortise mount

Holding force	3 000 N (~670 lbs)
Voltage	12/24 VDC
Current	500/250 mA
Locking Monitoring	Reed contact
Door position Monitoring	no
Internal timer	no
Sizes: LxWxH	188 x 39 x 27
Weight	~ 2 kgs

iGEM 1



Mortise mount

Holding force	3 000 N (~670 lbs)
Voltage	12/24 VDC
Current	500/250 mA
Locking Monitoring	no
Door position Monitoring	no
Internal timer	no
Sizes: LxWxH	188 x 39 x 27
Weight	~ 2 kgs