

5300 N

■ Right at the beginning, the original range for hi- security doors

- Corrosion proof (ISO tested)
- No residual magnetism
- Built-in MOV surge protection
- 10 years warranty

iGEM 4



Holding force	5 300 N (~ 1 200 lbs)
Voltage	12/24 VDC
Current	500/250 mA
Locking Monitoring	Led + Relay
Door position Monitoring	no
Internal timer	no
Sizes: LxWxH	268 x 73 x 40 mm
Weight	~ 4 kgs

iGEM 4 DSS



Holding force	5 300 N (~ 1 200 lbs)
Voltage	12/24 VDC
Current	500/250 mA
Locking Monitoring	Led + Relay
Door position Monitoring	Reed contact
Internal timer	no
Sizes: LxWxH	268 x 73 x 40 mm
Weight	~ 4 kgs

iGEM 4T



Holding force	5 300 N (~ 1 200 lbs)
Voltage	12/24 VDC
Current	500/250 mA
Locking Monitoring	Led + Relay
Door position Monitoring	no
Internal timer	Yes - 0 to 110 sec.
Sizes: LxWxH	268 x 73 x 40 mm
Weight	~ 4 kgs

iGEM 11



Holding force	5 300 N (~ 1 200 lbs)
Voltage	12/24 VDC
Current	500/250 mA
Locking Monitoring	no
Door position Monitoring	no
Internal timer	no
Sizes: LxWxH	268 x 73 x 40 mm
Weight	~ 4 kgs