

QMAG range
Basic - Surface: *Standard*



	MGI255 <i>IGEM 4000HS</i>	MGI251 <i>IGEM 4</i>	MGI250 <i>IGEM11</i>	MGI260 <i>IGEM 12</i>	<i>IGEM 4000NF</i>
Main features	5300N Range			2x5300N Range	5300N Range
Mounting	Surface				
Holding Force	4500N/~1010lbf/450kgf			2x4500N/~2x1010lbf/2x450kgf	4500N/~1010lbf/450kgf
Voltage	12/24V DC				24/48V DC
Current	500/250mA			2 x 500/250mA	250/125mA
Locking monitoring	Led + Relay			No	Reed Contact
Door position monitoring	Smart Chip + Relay			No	
NF S61937 (DAS for France)					Yes
Corrosion Proof	Salt spray test. ISO 9227, ASTM B-117 90				
NO magnetism residual	Guaranteed No residual Magnetism. First quality of steel, resin and copper. No need armature plate push button to release the door				
Built-in MOV Surge Protection	Yes				
Mechanical features					
Dimensions (LxWxH)	268x73x40mm			536x73x40mm	268x73x40mm
Weight	~ 2kgs			~ 8kgs	~ 4kgs
L Bracket (only)	AMLB 1			2 x AMLB 1	AMLB 1
Z + L Set bracket	AMZB 1			2 x AMZB 1	AMZB 1

MGI290
AMLB 1



**Mounting brackets for
IGEM3500, IGEM5700 & IGEM5700D**

	AMLB 1	AMZB 1
Type	L Bracket (only)	Z + L Set Bracket
Material	Extruded Aluminium anodised surface (not folded)	



MGI291
AMZB 1