

7500 N

The stainless steel heavy duty range for hi-security gates

- **Corrosion proof (ISO tested)**
- **IP 67**
- **AISI 316 magnet body**
- **No residual magnetism**
- **Built-in MOV surge protection**
- **10 years warranty**

iGEM 5000S



Surface mount - Side fixing

Holding force	7 500 N (~1 700 lbs)
Voltage	12/24 VDC
Current	500/250 mA
Locking Monitoring	Reed contact
Door position Monitoring	no
Internal timer	no
Sizes: LxWxH	225 x 63 x 44
Weight	~ 5 kgs

iGEM 5000F



Surface mount - Front fixing

Holding force	7 500 N (~1 700 lbs)
Voltage	12/24 VDC
Current	500/250 mA
Locking Monitoring	Reed contact
Door position Monitoring	no
Internal timer	no
Sizes: LxWxH	225 x 63 x 44
Weight	~ 5 kgs

iGEM 5000G



GATELOCK Surface Mount Universal fix.

Holding force	7 500 N (~1 700 lbs)
Voltage	12/24 VDC
Current	500/250 mA
Locking Monitoring	Reed contact
Door position Monitoring	no
Internal timer	no
Sizes: LxWxH	225 x 63 x 44
Weight	~ 5 kgs