

	MGM300 IGEM 3500	MGM530 IGEM 5700	IGEM 5700D
Main features	3000N Range	5300N Range	2x5300N Range
Mounting	Surface		
Holding Force	2430N/~545lbf/243kgf	4500N/~1010lbf/450kgf	2 x4500N/2x~1010lbf/2x450N
Voltage	12/24V DC		
Current	500/250mA		2 x 500/250mA
Locking monitoring	Large L shaped LED for long distance status + Relay		2 Large L shaped LED for long distance status + 2 Relay
Door position monitoring	No		
Corrosion Proof	Salt spray test. ISO 9227, ASTM B-117 90		
NO magnetism residual	Guaranteed No residual Magnetism. First quality of steel, resin and copper. No need armature plate push button to release the door		
Built-in MOV Surge Protection	Yes		
Mechanical features			
Dimensions (LxWxH)	238 x 26 x 48mm	268 x 73 x 40mm	536 x 73 x 40mm
Weight	~ 2kgs	~ 4kgs	~ 8kgs
L Bracket (only)	AMLB4		
Z + L Set bracket	AMZB4-LP	AMZB1-LP	AMZB1-LP



AMLB4

**Mounting brackets for
IGEM3500, IGEM5700 & IGEM5700D**

	AMLB4	AMZB1-LP	AMZB4-LP
Type	L Bracket (only)	Z + L Set Bracket	
Material	Extruded Aluminium anodised surface (not folded)		



AMZB1-LP /
AMZB4-LP