

Voeding 12 Vdc-1A in kleine behuizing van 70x40x30 mm Alimentation 12 Vcc-1A dans un petit boîtier de 70x40x30 mm

Features

Power (W): 12,00

Input

Input voltage: 100,00÷240,00 Vac

Frequency (Hz): 50÷60

Input current (A): 0,12

Output

Output voltage: 12,00 +15% regolabile Vdc

Rated current: 1,00

Connections

Input:

Screw terminals

Output:

Screw terminals

Suggested applications:

Videocameras

Installation:

Into 3 modules flush-mounted box

Into electrical connector blocks

Dimensions

Dimensions (mm): W 70,00 x H 30,00 x D 50,00

Weight (kg): 0,11

Standards:

2006/95/EC Directive

2004/108/EC Directive

CEI EN 60950-1



Features

Technology:

Switching

Efficiency (%): 80,00

Input protections:

Fuse

Output protections:

Fuse - Current limitation

Signaling:

LED

IP rating: IP20

Mtbf (h): 100000

Working temperature (°C): -20 - 40

Relative humidity (%): 0 - 90

rev04

onder voorbehoud van wijziging - de hierboven vermelde gegevens zijn louter informatief en niet bindend / sous réserve de modifications - les données ci-dessus ne sont mentionnées qu'à titre informatif, sans engagement

UW PARTNER IN TOEGANGSCONTROLE – VOTRE PARTENAIRE EN CONTROLE D' ACCES