

Omzetter 12/28Vdc - 3/4,5/6/7,5/9/13,8Vdc - 1A
Convertisseur 12/28Vcc - 3/4,5/6/7,5/9/13,8Vcc - 1A

Input

Input voltage: 12,00÷28,00 Vdc

Peak current (A): 1,50

Output

Output voltage: 3/4,5/6/7,5/9/13,8 Vdc

Rated current: 1,00

Current protection/Limitation: 2

Connections

Input:

M5 threaded insert

Output:

M5 threaded insert

Suggested applications:

Installation:

Dimensions

Dimensions (mm): W 80,00 x H 35,00 x D 115,00

Weight (kg): 0,20

Standards:

2006/95/EC Directive

2004/108/EC Directive

CEI EN 60950-1

CEI EN 61558-1



Features

Technology:

Linear

Efficiency (%): 80,00

No-load absorption: 0,02A

Output protections:

Overload - Short-circuit

Signaling:

LED

IP rating: IP20

Working temperature (°C): -10 - 40

Relative humidity (%): 0 - 95

rev04

onder voorbehoud van wijziging - de hierboven vermelde gegevens zijn louter informatief en niet bindend / sous réserve de modifications - les données ci-dessus ne sont mentionnées qu'à titre informatif, sans engagement

UW PARTNER IN TOEGANGSCONTROLE – VOTRE PARTENAIRE EN CONTROLE D' ACCES