

UPS voor alle toepassingen 1700 VA UPS pour toutes applications 1700 VA

Capacity (VA): 1700,00

Input

Input voltage: 175,00÷285,00 Vac

Frequency (Hz): 50

Input current (A): 7,00

Output

Output voltage: 230,00 ±2% Vac

Frequency (Hz): 50 same as input

Connections

Input:

Schuko plug

Output:

IEC320 sockets

Suggested applications:

Installation:

Desktop

Dimensions

Dimensions (mm): W 192,00 x H 340,00 x D 460,00

Weight (kg): 34,50

Standards:

2006/95/EC Directive

2004/108/EC Directive

CEI EN 62040-1-1

CEI EN 62040-2

CEI EN 62040-3

CEI EN 60204-1

CEI EN 61000-3-3

CEI EN 61000-4-5

CEI EN 50272-2



Features

Backup time (minutes): 12,00

Wave form: Sine wave

Thd (%): 3,00

Technology:

On-Line

Input protections:

Breaker

Output protections:

Overload

Alerts:

Emergency mode - Battery output sensed - Overload - Abnormal operation - Fault

Signaling:

Acoustic signaling - LCD display

Measuring instruments:

Digital voltemeter

Battery input voltage (Vdc): 96

Battery type: Sealed lead acid, maintenance free batteries

Audible noise (dB/m): 50at 1

IP rating: IP20

Working temperature (°C): 0 - 40

Relative humidity (%): 0 - 95

