

Noodvoeding 1000VA - 600W Alimentation de secours 1000VA - 600W

Features

Capacity (VA): 1000,00

Power (W): 600,00

Input

Input voltage: 170,00÷270,00 Vac

Frequency (Hz): 50÷60

Output

Output voltage: 230,00 ±5% Vac

Frequency (Hz): 50÷60

Rated current: 2,50

Maximum surge current (A): 8,00

Connections

Input:

Terminal board

Output:

Terminal board

Suggested applications:

Domotics

Installation:

Wall-mounted (with-wall mounted tracks)

Dimensions

Dimensions (mm): W 294,00 x H 443,00 x D 176,00

Weight (kg): 14,50

Standards:

2006/95/EC Directive

2004/108/EC Directive

CEI EN 62040-1-1

CEI EN 62040-2

CEI EN 62040-3

CEI EN 50272-2



Features

Wave form: Sine wave

Technology:

Line-Interactive

Transfer time (ms): 2,00

Efficiency (%): 97,00

Input protections:

Battery fuse

Output protections:

Overload - Short-circuit - Overtemperature

Alerts: 48,00

Back-up operation - Battery voltage out of range - Thermal protection - Overload - Short-circuit - Abnormal operation - Fault

Remote control functions:

NO dry contact for emergency mode

Signaling:

Acoustic signaling - LCD display

Battery input voltage (Vdc): 24

Maximum batteries capacity (Ah):

Battery type: Sealed lead acid, maintenance free batteries

Audible noise (dB/m): 40at 1

IP rating: IP20

Cooling: Forced air convection

Working temperature (°C): 0 - 40

Relative humidity (%): 5 - 95



rev04

onder voorbehoud van wijziging - de hierboven vermelde gegevens zijn louter informatief en niet bindend / sous réserve de modifications - les données ci-dessus ne sont mentionnées qu'à titre informatif, sans engagement

UW PARTNER IN TOEGANGSCONTROLE – VOTRE PARTENAIRE EN CONTROLE D' ACCES