

Voeding 12 Vdc - 12 A - DIN-rail montage Alimentation 12 Vcc - 12 A pour rail DIN

Features

Input

Input voltage: 110/220 Vac

Frequency (Hz): 50÷60

Input current (A): 1,40

Peak current (A): 44,00

Output

Output voltage: 12,00 +20% regolabile Vdc

Rated current: 12,00

Connections

Input:

Screw terminals

Output:

Screw terminals

Suggested applications:

Production plants

Release coils

Domotics

Electric locks

Solenoid valves

Alarm systems

Sensors

Videocameras

CCTV

Installation:

Wall-mounted

On DIN rail

Dimensions

Dimensions (mm): W 75,00 x H 121,00 x D 125,00

Weight (kg): 0,72

Standards:

2006/95/EC Directive



2004/108/EC Directive

CEI EN 60950-1

CEI EN 61000-3-3

CEI EN 61000-4-5

IEC 801-2

IEC 801-3

IEC 801-4

Features

Technology:

Switching

Transfer time (ms): 2,00

Hold-up time (ms): 20,00

Ripple (mV_{p-p}): 100,00

Efficiency (%): 78,00

Power dissipation (W): 43,00

Input protections:

Fuse

Output protections:

Thermal - Overload - Short-circuit - Current limitation

Remote control functions:

Dry contact for alerts

Signaling:

LED

IP rating: IP20

Cooling: Natural air convection

Mtbf (h): 100000

Working temperature (°C): -20 - 50

Relative humidity (%): 5 - 95

rev04

onder voorbehoud van wijziging - de hierboven vermelde gegevens zijn louter informatief en niet bindend / sous
réserve de modifications - les données ci-dessus ne sont mentionnées qu'à titre informatif, sans engagement

UW PARTNER IN TOEGANGSCONTROLE – VOTRE PARTENAIRE EN CONTROLE D' ACCES