

Voeding 12 Vdc - 4 x 1 A - DIN-rail montage Alimentation 12 Vcc - 4 x 1 A pour rail DIN

Features

Power (W): 48,00

Input

Input voltage: 100,00÷240,00 Vdc

Frequency (Hz): 50÷60

Output

Output voltage: 12,00÷14,00 Vdc

Frequency (Hz): 50÷60

Connections

Input:

Terminal board

Output:

Terminal board

Suggested applications:

Engines

Sensors

Intrusion detection systems

Videocameras

CCTV

Installation:

On DIN rail

Panel, cabinets etc..

Dimensions

Dimensions (mm): W 124,00 x H 90,00 x D 65,00

Weight (kg): 0,35

Standards:

CEI EN 55011



Features

Technology:

Switching

Ripple (mV_{p-p}): 10,00

Efficiency (%): 81,00

Power dissipation (W): 11,00

Output protections:

Thermal - Overload - Short-circuit

Signaling:

LED

IP rating: IP20

Working temperature (°C): -10 - 40

rev01

onder voorbehoud van wijziging - de hierboven vermelde gegevens zijn louter informatief en niet bindend / sous réserve de modifications - les données ci-dessus ne sont mentionnées qu'à titre informatif, sans engagement

UW PARTNER IN TOEGANGSCONTROLE – VOTRE PARTENAIRE EN CONTROLE D' ACCES