

Voeding 24 Vdc – 2,5 A - DIN-rail montage Alimentation 24 Vcc – 2,5 A pour rail DIN

Input

Input voltage: 100,00÷240,00 Vac

Frequency (Hz): 50÷60

Input current (A): 0,60



Output

Output voltage: 24,00 +15% regolabile Vdc

Rated current: 2,50

Connections

Input:

Screw terminals

Output:

Screw terminals

Suggested applications:

Production plants

Release coils

Domotics

Electric locks

Solenoid valves

Alarm systems

Sensors

Intrusion detection systems

Videocameras

CCTV

Installation:

On DIN rail

Dimensions

Dimensions (mm): W 65,00 x H 90,00 x D 70,00

Weight (kg): 0,18

Standards:

2006/95/EC Directive

2004/108/EC Directive

CEI EN 60950-1

CEI EN 61000-3-2

CEI EN 61000-3-3

CEI EN 61000-4-5

IEC 801-2

IEC 801-4

Features

Technology:

Switching

Ripple (mV_{p-p}): 90,00

Efficiency (%): 86,00

Power dissipation (W): 7,00

Modules number: 4

Input protections:

Fuse

Output protections:

Thermal - Overload - Short-circuit - Current limitation

Signaling:

LED

IP rating: IP20

Cooling: Natural air convection

Mtbf (h): 100000

Working temperature (°C): -10 - 40

Relative humidity (%): 5 - 95

