

## Voeding 24 Vdc – 4,5 A - DIN-rail montage Alimentation 24 Vcc – 4,5 A pour rail DIN

### Features

#### Input

Input voltage: 110/230 Vac

Frequency (Hz): 50+60

Input current (A): 0,90

#### Output

Output voltage: 24,00 +15% regolabile Vdc

Rated current: 4,50

#### Connections

Input:

Screw terminals

Output:

Screw terminals

#### Suggested applications:

Production plants

Release coils

Domotics

Electric locks

Solenoid valves

Alarm systems

Sensors

Intrusion detection systems

Videocameras

CCTV

#### Installation:

On DIN rail

#### Dimensions

Dimensions (mm): W 125,00 x H 90,00 x D 70,00

Weight (kg): 0,36

#### Standards:

2006/95/EC Directive

2004/108/EC Directive



CEI EN 60950-1

CEI EN 61000-3-2

CEI EN 61000-3-3

CEI EN 61000-4-5

IEC 801-2

IEC 801-4

#### Features

Technology:

Switching

Ripple (mV<sub>p-p</sub>): 110,00

Efficiency (%): 86,00

Power dissipation (W): 11,00

Modules number: 7

Input protections:

Fuse

Output protections:

Thermal - Overload - Short-circuit - Current limitation

Signaling:

LED

IP rating: IP20

Cooling: Natural air convection

Mtbf (h): 100000

Working temperature (°C): -10 - 40

Relative humidity (%): 5 - 95

rev04

onder voorbehoud van wijziging - de hierboven vermelde gegevens zijn louter informatief en niet bindend / sous  
réserve de modifications - les données ci-dessus ne sont mentionnées qu'à titre informatif, sans engagement

UW PARTNER IN TOEGANGSCONTROLE – VOTRE PARTENAIRE EN CONTROLE D' ACCES