

Voeding 24 Vdc – 1 A - DIN-rail montage Alimentation 24 Vcc – 1 A pour rail DIN

Features

Input

Input voltage: 100,00÷240,00 Vdc

Frequency (Hz): 50

Frequency (Hz): 50÷60

Output

Output voltage: 24,00 +15% regolabile Vdc

Rated current: 1,00

Connections

Input:

Screw terminals

Output:

Screw terminals

Suggested applications:

Production plants

Release coils

Domotics

Electric locks

Solenoid valves

Alarm systems

Sensors

Installation:

On DIN rail

Dimensions

Dimensions (mm): W 35,55 x H 90,00 x D 66,00

Standards:

2006/95/EC Directive

2004/108/EC Directive

CEI EN 60950-1



CEI EN 61000-3-2

CEI EN 61000-3-3

CEI EN 61000-4-5

IEC 801-2

IEC 801-4

Features

Technology:

Switching

Hold-up time (ms): 15,00

Ripple (mV_{p-p}): 100,00

Efficiency (%): 86,00

Power dissipation (W): 3,90

Modules number: 2

Input protections:

Fuse

Output protections:

Thermal - Overload - Short-circuit - Current limitation

Signaling:

LED

IP rating: IP20

Cooling: Natural air convection

Working temperature (°C): -10 - 40

Relative humidity (%): 5 - 95

rev04

onder voorbehoud van wijziging - de hierboven vermelde gegevens zijn louter informatief en niet bindend / sous réserve de modifications - les données ci-dessus ne sont mentionnées qu'à titre informatif, sans engagement

UW PARTNER IN TOEGANGSCONTROLE – VOTRE PARTENAIRE EN CONTROLE D' ACCES