

DEIMOS SR

For sliding gates weighing up to 500 kg,
RESIDENTIAL USE



DEIMOS. Technical Data

Power: 230V $\pm 10\%$ 50Hz
Absorbed power: 290W
Impact reaction: mechanical friction
Door speed: 8.5m/min
Protection level: IP24
Controller weight: 15 Kg
Incorporated control panel: MIZAR

DEIMOS SR Actuator will substitute the **COMPAT SR** actuator

In comparison to the **COMPAT SR**...

1. The NEW DESIGN improves the mechanical characteristics of the casing, making it more sturdy, especially during transportation.
2. NEW RELEASE KNOB requires use of standard BFT trilobed key, thus improving burglary safety and easier use by the final client.
3. The MIZAR control board remains, but its position inside the casing has changed. IT CHANGES FROM A LATERAL POSITION TO A FRONTAL POSITION WITH RESPECT TO THE MOTOR. This therefore improves accessibility to the control panel.

DEIMOS KIT. The KIT includes:

DEIMOS SR (substitutes COMPAT SR)
CELLULA 130 photocell (substitutes FL 130)
MITTO2 433 Mhz rolling code remote control (substitutes TO2)
INTRICI 433 Mhz rolling code receiver (substitutes RO1)
INTRO key selector (substitutes PC2)
LAMPO PA blinker (substitutes PULSAR PA)
SL433 antenna (substitutes ST 30.8)