

DEIMOS BT-24 V

For sliding gates weighing up to 300 Kg,
RESIDENTIAL USE



DEIMOS BT Actuator
will substitute the **SB300** actuator

In comparison to the **SB 300**...

1. The **NEW DESIGN** improves the mechanical characteristics of the casing, making it more solid, especially during transportation.
2. The **NEW RELEASE KNOB** requires utilisation of a standard BFT trilobed key, thereby improving protection against burglary and easier use by the final client.

DEIMOS BT – Technical Data

Power: 230V $\pm 10\%$ 50Hz

Motor: 24V dc

Absorbed power: 70W

Leaf speed: 12m/min

Impact reaction: electronic torque limiter

Protection Level: IP24

Controller Weight: 7 Kg.

Incorporated control board: **QSC**

NOTE: the QSC board includes the 64 rolling code receiver.

ACCESSORIES

SB BAT: Batteries and battery charging board kit for functioning of sliding door in the absence of electric power.

The **DEIMOS BT KIT**. The KIT includes:

A **DEIMOS BT** motor (substitutes the SB 300)

CELLULA 130 photocell (substitutes the FL 130)

MITTO 2 433 Mhz rolling code remote control (substitutes the TO2)

INTRO key selector (substitutes the PC2)

LAMPO PA blinker (substitutes the PULSAR PA)

SL433 antenna (substitutes the ST 30.8)